



## Industrial grade electric strikes for use with cylindrical locks, mortise locks\* and mortise exit devices

700 Series



fire rated



UL 1034  
burglary listed



grade 1

### Applications

#### 712

For use with 1/2" to 5/8" throw latchbolts in hollow-metal frame applications

- 1/2" keeper standard

#### 712-75

For use with 1/2", 5/8", or 3/4" throw latchbolts in hollow-metal frame applications

- 3/4" keeper standard

#### 732

For use with 1/2" to 5/8" throw latchbolts in wood frame applications. Features an offset solenoid

- 1/2" keeper standard

#### 732-75

For use with 1/2", 5/8", or 3/4" throw latchbolts in wood frame applications. Features an offset solenoid

- 3/4" keeper standard

*\*Note: These products will require relocation of the center line when used with mortise locks. Consult HES customer support regarding use with Best 40 Series.*



## Specifications

- UL 10C fire-rated, 3 hour single door (fail secure only)
- UL 10C fire-rated, 3 hour double door (fail secure only)
- CAN4-S104 (ULC-S104) fire door conformant
- UL1034, burglary-resistant listed
- ANSI/BHMA A156.31, Grade 1
- DOD approved
- New York City accepted
- NFPA-252 fire door conformant
- ASTM-E152 fire door conformant

## Electrical

- .29 Amps @ 12VDC continuous duty
- .15 Amps @ 24VDC continuous duty

## Standard Features

- Tamper resistant, heavy-duty construction
- Constructed entirely of stainless steel for strength and corrosion resistance
- Static strength 1,500 lbs.
- Dynamic strength 70 ft-lbs.
- Horizontally adjustable keeper to allow for door and frame misalignment
- 1/2" keeper depth (712 and 732)
- 3/4" keeper depth (712-75 and 732-75)
- Non-handed
- Fail Secure (standard)
- Plug-in connector
- Five year limited warranty

## Optional Features

- Fail Safe
- LBMLCM - Latchbolt & Locking Cam Monitor

## Accessories

- 150 - Strike latch guard
- 152 - Universal mounting tabs
- 2001-1 - Wire-in bridge rectifier
- 2001M - Plug-in bridge rectifier
- 2004M - ElectroLynx™ adapter
- 2005M - SMART Pac II™
- 2006M - Plug-in buzzer

## Finishes

- 630 - Satin stainless steel finish
- 605 - Bright brass finish
- 606 - Satin brass finish
- 612 - Satin bronze finish
- 613 - Bronze toned finish
- 629 - Bright stainless steel finish